



USPI 88SV-SS Filtration System

- Removes moisture (up to 5 qts per element)
- Removes solid particles 1-3 μ and above (up to 12-14 lbs per element)
- Protects and preserves oil additive package
- Reduces operating temperature
- Significantly extends equipment and fluid life

DRAIN VALVE
OIL SAMPLING PORT

NOT SHOWN
PRESSURE RELIEF VALVE
FLOW METER
SIZED TO UNIT (1-20 GPM)
60 MESH SS Y-STRAINER

Stationary Filtration^{for} Vacuum Washdown

Vacuum pumps operate continuously in adverse conditions with moisture and high heat. In some applications, vacuum pumps must be cleaned by water or caustic chemicals. USPI has designed several stainless steel units to provide dedicated ultra-fine water-removing filtration for critical equipment even in harsh environments.

DIMENSIONS: 18.25"W x 47"H x 23"D
WEIGHT: ~100lbs



USPI AFA Series Filter Element

- Removes solid particles 1-3 microns and larger
 - Holds up to 12-14 lbs of solids per element
 - Holds up to 5 qts of water per element
- SOLD SEPARATELY

maximize your USPI Vacuum Pump Washdown Filtration System with...



USPIFLUIDS

USPI offers a complete line of custom-formulated synthetic lubricants designed to withstand vacuum pump operating temperatures and moisture levels. H-1 food grade and non-food grade options available.



OILSAMPLING

USPI provides free comprehensive quarterly oil analysis with the purchase of our vacuum pump lubricants. Independent oil analysis will help you make condition-based decisions in a predictive-proactive maintenance program.



OEMFILTERS

USPI offers OEM replacement air filters, oil filters, and exhaust filters for vacuum pumps that meet or exceed manufacturer specifications at significantly lower costs.