



USPETROLON INDUSTRIAL, INC.

447 N. 66th Unit 3 Lincoln, NE 68505

TOLL-FREE: (800) 755-4572 PHONE: (402) 423-6375 FAX: (402) 423-6661

WEB: www.uspetrolon.com EMAIL: sales@uspetrolon.com

NH3 COMPRESSOR SOLUTIONS

USPI 1009-68SC Compressor Oil 1000AMM Filtration System

USPI 1009-68 SC is a custom-blended, highly refined, de-waxed, chemically inert semi-synthetic compressor lubricant. It has a unique closed molecular structure making it extremely thermal and oxidatively stable. It provides better lubricity than conventional refrigeration oils for reciprocating, rotary screw and vane compressors, resulting in:

- Reduced Downtime
- Up To 50% Less Oil Carryover
- Cleaner Systems
- Increased Liquid Pump Flow
- Non Carbonization
- Reduced Wear, Longer Machine Life
- Seal Conditioning with Patented Additive Package
- Coupled with Comprehensive Oil Analysis and Monitoring

A 1000AMM Filtration System in-line, kidney-loop filtration unit coupled with our depth style filter elements will meet your needs and provide you increased productivity with cost savings, regardless of your NH3 compressor application. It will:

- Remove Moisture (up to 5 quarts/element)
- Remove Solid Particles 1-3 microns and above (12lbs/element)
- Protect the Additive Package • Reduce Operating Temperature
- Significantly Extend Compressor and Fluid Life
(over 15 years with NO oil changes)



USPI D1000AMM pictured

1000AMM Series Specifications

- Powder-Coated Steel Housing
- Rigid Steel Piping
- Flow Meter (sized to unit): 1-5 or 1-10 GPM
- Pressure Gauges to Monitor Element Pressures
- Oil Sampling Port
- Flow Control Device

- Dimensions:
S1000AMM: 24"W x 41-1/2"H x 17"D
D1000AMM: 26"W x 41-1/2"H x 17"D
T1000AMM: 26"W x 41-1/2"H x 24-1/2"D
- Weight (varies by unit): ~85-185lbs.
- FILTER ELEMENTS SOLD SEPARATELY

1000AMM Series Units

- S1000AMM:** for Reservoirs ~1-120 gallons
 - D1000AMM:** for Reservoirs ~121-260 gallons
 - T1000AMM:** for Reservoirs ~261-390 gallons
- Custom-sized units are available