



USPETROLON INDUSTRIAL, INC.

447 N. 66th Unit 3 Lincoln, NE 68505

TOLL-FREE: (800) 755-4572 PHONE: (402) 423-6375 FAX: (402) 423-6661

WEB: www.uspetrolon.com EMAIL: sales@uspetrolon.com

USPI Inline Filtration

Stationary Filtration Systems for Glycol

Is there an accumulation of suspended sludge within your glycol system? Are you experiencing excessive operating and maintenance costs? The 88 Glycol series will greatly extend your pump life by preventing the accumulation of solid sin the absorber and regeneration equipment, significantly reducing operating and maintenance costs.

An 88 Glycol Series in-line, kidney-loop filtration unit coupled with our depth style filter elements will meet your needs and provide you increased productivity with cost savings. In addition, we offer a comprehensive oil monitoring and analysis program with personal service to ensure you get maximum life from your equipment, oils and filter elements.

88 Glycol Series Units

- 88SG:** for Reservoirs ~1-120 gallons
- 88DG:** for Reservoirs ~121-360 gallons
- 88QG:** for Reservoirs ~361-720 gallons
- 88DG+2:** for Reservoirs ~360-720 gallons
- 88QG+2:** for Reservoirs ~721-1440 gallons

88 Glycol Series Specifications

- Stainless Steel Housing(s)
- Steel or Stainless Steel Mounting Bracket
- Stainless Steel Piping
- Oil Sampling Port
- Flow Meter (sized to unit): 1-20 GPM
- Pressure Safety Valve
- Stainless Steel Ball Valve(s)
- Drain Valve
- Pressure Gauges
- Pump: size varies by design
- Motor: Choose between Air, 120/240V 1Ph., 230-460V 3Ph.
- Dimensions (for 88S): 19"Wx44-1/2"Hx14"D
- Weight (varies by unit): ~85-185lbs.
- FILTER ELEMENTS SOLD SEPARATELY



USPI 88DG+2 pictured