



USPETROLON INDUSTRIAL, INC.

447 N. 66th Unit 3 Lincoln, NE 68505

TOLL-FREE: (800) 755-4572 PHONE: (402) 423-6375 FAX: (402) 423-6661

WEB: www.uspetrolon.com EMAIL: sales@uspetrolon.com

USPI Inline Filtration

Stationary Filtration Systems for Washdown

Some environments require washdown but without the caustic substances used in other washdown environments. The 88 Washdown series will give you the benefits of ultra-fine filtration with a user friendly system that's easy to install and operate in your *non-caustic* washdown applications.

An 88 Washdown Series in-line, kidney-loop filtration unit coupled with our depth style filter elements will meet your needs and provide you increased productivity with cost savings. In addition, we offer a comprehensive oil monitoring and analysis program with personal service to ensure you get maximum life from your equipment, oils and filter elements.



USPI 88DG+2 pictured

88 Washdown Series Units

- 88SG:** for Reservoirs ~1-120 gallons
- 88DG:** for Reservoirs ~121-360 gallons
- 88QG:** for Reservoirs ~361-720 gallons
- 88DG+2:** for Reservoirs ~360-720 gallons
- 88QG+2:** for Reservoirs ~721-1440 gallons

88 Washdown Series Specifications

- Stainless Steel Housing(s)
- Steel or Stainless Steel Mounting Bracket
- Stainless Steel Piping
- Oil Sampling Port
- Flow Meter (sized to unit): 1-20 GPM
- Pressure Safety Valve
- Stainless Steel Ball Valve(s)
- Drain Valve
- Pressure Gauges
- Pump: size varies by design
- Motor: Choose between Air, 120/240V 1Ph., 230-460V 3Ph.
- Dimensions (for 88S): 19"Wx44-1/2"Hx14"D
- Weight (varies by unit): ~85-185lbs.
- FILTER ELEMENTS SOLD SEPARATELY